



Gear Oil

Point® Gear Oil is a multipurpose, extreme-pressure, API GL-5 automotive gear lubricant. It is formulated to meet the lubrication requirements of passenger car and truck axles with conventional differentials. It is specifically designed for use in axles with hypoid gear sets.

Applications

- Conventional differentials on passenger cars, trucks and buses
- Differentials, final drives and transfer cases on some off-highway equipment

Gear Oil meets or exceeds the requirements of:

- API Service GL-5

Note: For all applications involving limited-slip differentials, the manufacturer's specified gear lubricant or supplemental additive should be used. Refer to the owner's manual for specific requirements.

**Automotive
Gear Oil, API GL-5**

Contact Information

**U.S. Customer
Service:
1-800-822-6457**

**U.S. Technical
Services Hot Line:
1-877-445-9198**

**E-mail address:
*lubricants@
phillips66.com***

www.phillips66lubricants.com

600 N. Dairy Ashford • 2W9000 • Houston, TX 77079

Point® Gear Oil

Typical Properties

SAE Grade	80W-90	85W-140
Specific Gravity @ 60°F	0.880	0.896
Density, lbs/gal @ 60°F	7.33	7.46
Color, ASTM D1500	2.5	2.5
Flash Point (COC), °C (°F)	212 (414)	216 (421)
Pour Point, °C (°F)	-30 (-22)	-12 (-10)
Viscosity, Brookfield		
cP @ -26°C	65,000	—
cP @ -12°C	—	36,000
Viscosity, Kinematic		
cSt @ 40°C	137	345
cSt @ 100°C	13.9	25.9
Viscosity Index	97	97

Health and Safety Information

For recommendations on safe handling and use of this product, please refer to the Material Safety Data Sheet via <http://w3apps.phillips66.com/NetMSDS>.

Typical properties are average values only and do not constitute a specification. Minor variations that do not affect product performance are to be expected during normal manufacture, and at different blending locations. Product formulations are subject to change without notification.

Copyright © 2012 Phillips 66 Company. Phillips 66, Point and their respective logos are trademarks of Phillips 66 Company in the U.S.A. and other countries.

