



Premier Full Synthetic Motor Oil

Point® Premier Full Synthetic Motor Oil is a very high-quality, full-synthetic, API SM/ILSAC GF-4 engine oil designed for use in passenger cars and light trucks under all operating conditions.

Premier Full Synthetic Motor Oil provides enhanced performance benefits compared with conventional (all-mineral) engine oils. These benefits include better oxidation resistance and thermal stability at high temperatures for improved protection against viscosity breakdown and deposit formation; lower volatility for reduced oil consumption; and better low-temperature pumpability for easier starting and faster oil circulation at low temperatures.

Applications

- Passenger cars, light trucks and sport utility vehicles, especially when operating under severe conditions

Premier Full Synthetic Motor Oil meets or exceeds the requirements of:

- API Service SM, SL, CF
- Energy Conserving, ILSAC GF-4

**Full-Synthetic
Passenger Car
Engine Oil**

Contact Information

**U.S. Customer
Service:
1-800-822-6457**

**U.S. Technical
Services Hot Line:
1-877-445-9198**

**E-mail address:
*lubricants@
conocophillips.com***

www.conocophillipslubricants.com

600 N. Dairy Ashford • 2W9000 • Houston, TX 77079

Point® Premier Full Synthetic Motor Oil

Typical Properties

SAE Grade	5W-30	10W-30
Specific Gravity @ 60°F	0.854	0.864
Density, lbs/gal @ 60°F	7.11	7.20
Color, ASTM D1500	3.0	3.0
Flash Point (COC), °C (°F)	235 (455)	235 (455)
Pour Point, °C (°F)	-36 (-33)	-36 (-33)
Viscosity, Kinematic		
cSt @ 40°C	60.0	65.0
cSt @ 100°C	10.0	10.6
Viscosity Index	166	166
Cold Cranking Viscosity, cP	4,500	4,900
@ (°C)	(-30)	(-25)
High-Temp/High-Shear Viscosity, cP @ 150°C	3.0	3.2
Sulfated Ash, ASTM D874, wt %	0.92	0.92
Total Base Number (TBN), ASTM D2896	8.8	8.8
Phosphorus, wt %	0.075	0.075
Zinc, wt %	0.084	0.045

Health and Safety Information

For recommendations on safe handling and use of this product, please refer to the Material Safety Data Sheet via <http://w3.conocophillips.com/NetMSDS>.

Typical properties are average values only and do not constitute a specification. Minor variations that do not affect product performance are to be expected during normal manufacture, and at different blending locations. Product formulations are subject to change without notification.

Copyright © 2010 ConocoPhillips Company. The ConocoPhillips logo and Point are trademarks of ConocoPhillips Company in the U.S.A. and other countries.