



Truck Tested Motor Oil, SAE 30

Point® Truck Tested Motor Oil, SAE 30, is a high-quality diesel engine oil designed for use in older 4-stroke cycle diesel engines that specify a monograde API Service CF or CD quality oil. It also may be used in some 2-stroke cycle diesel engines operating in cold climates, and in some heavy-duty manual transmissions in trucks and buses.

Truck Tested Motor Oil, SAE 30, is formulated to provide excellent wear protection, to minimize the formation of sludge and varnish, to protect against bearing corrosion, and to resist foaming. The low ash content helps minimize the formation of valve deposits and keep intake ports clean to maintain good power output in 2-stroke cycle applications.

Applications

- Older 4-stroke cycle diesel engines where the manufacturer specifies a monograde API CF or CD quality oil
- Some 2-stroke cycle diesel engines operating in cold climates
- Some heavy-duty manual transmissions in trucks and buses

Truck Tested Motor Oil, SAE 30, meets or exceeds the requirements of:

- API Service CF, CF-2 (obsolete)

**Low-Ash Diesel
Engine Oil**

Contact Information

**U.S. Customer
Service:
1-800-822-6457**

**U.S. Technical
Services Hot Line:
1-877-445-9198**

**E-mail address:
*lubricants@
phillips66.com***

www.phillips66lubricants.com

600 N. Dairy Ashford • 2W9000 • Houston, TX 77079

Point® Truck Tested Motor Oil

Typical Properties

SAE Grade	30
Specific Gravity @ 60°F	0.879
Density, lbs/gal @ 60°F	7.32
Color, ASTM D1500	L 4.0
Flash Point (COC), °C (°F)	240 (464)
Pour Point, °C (°F)	-33 (-27)
Viscosity, Kinematic	
cSt @ 40°C	92.0
cSt @ 100°C	11.0
Viscosity Index	115
High-Temp/High-Shear Viscosity, cP @ 150°C	3.6
Sulfated Ash, ASTM D874, wt %	1.0
Total Base Number (TBN), ASTM D2896	8.1
Zinc, wt %	0.109

Health and Safety Information

For recommendations on safe handling and use of this product, please refer to the Material Safety Data Sheet via <http://w3apps.phillips66.com/NetMSDS>.

Typical properties are average values only and do not constitute a specification. Minor variations that do not affect product performance are to be expected during normal manufacture, and at different blending locations. Product formulations are subject to change without notification.

Copyright © 2012 Phillips 66 Company. Phillips 66, Point and their respective logos are trademarks of Phillips 66 Company in the U.S.A. and other countries.

