



## Truck Tested Motor Oil, SAE 15W-40

Point® Truck Tested Motor Oil, SAE 15W-40, is a high-quality API CJ-4 engine oil developed for use in four-stroke cycle diesel engines designed to meet 2007 and later EPA on-highway exhaust emission standards. It is specially formulated to protect exhaust aftertreatment devices such as diesel particulate filters and diesel oxidation catalysts. It is backward serviceable for use in older diesel equipment with conventional, non-EGR engines, and also may be used in mixed fleets with both diesel and gasoline-fueled vehicles.

### ***Applications***

- On-highway diesel trucks equipped with EGR and exhaust aftertreatment devices
- Older on-highway and off-road diesel equipment with conventional, non-EGR engines
- Gasoline engines where the manufacturer specifies an SAE 15W-40 viscosity grade engine oil

Truck Tested Motor Oil, SAE 15W-40, meets or exceeds the requirements of:

- API Service CJ-4, CI-4 with CI-4 PLUS, CI-4, CH-4, SN

**Heavy-Duty Fleet  
Engine Oil For  
Low-Emission  
Engines**

### **Contact Information**

**U.S. Customer  
Service:  
1-800-822-6457**

**U.S. Technical  
Services Hot Line:  
1-877-445-9198**

**E-mail address:  
*lubricants@  
conocophillips.com***

***www.conocophillipslubricants.com***

600 N. Dairy Ashford • 2W9000 • Houston, TX 77079

## Point® Truck Tested Motor Oil

### Typical Properties

SAE Grade	15W-40
Specific Gravity @ 60°F	0.880
Density, lbs/gal @ 60°F	7.33
Color, ASTM D1500	4.0
Flash Point (COC), °C (°F)	227 (441)
Pour Point, °C (°F)	-38 (-36)
Viscosity, Kinematic	
cSt @ 40°C	116
cSt @ 100°C	15.2
Viscosity Index	137
Cold Cranking Viscosity, cP @ -20°C	6,500
High-Temp/High-Shear Viscosity, cP @ 150°C	4.3
Sulfated Ash, ASTM D874, wt %	0.97
Total Base Number (TBN), ASTM D2896	8.4
Zinc, wt %	0.121

### Health and Safety Information

For recommendations on safe handling and use of this product, please refer to the Material Safety Data Sheet via <http://w3.conocophillips.com/NetMSDS>.

---

Typical properties are average values only and do not constitute a specification. Minor variations that do not affect product performance are to be expected during normal manufacture, and at different blending locations. Product formulations are subject to change without notification.

Copyright © 2011 ConocoPhillips Company. The ConocoPhillips logo and the Point Lubricants logo are trademarks of ConocoPhillips Company in the U.S.A. and other countries.